

Air -/ Water Heat Exchanger RK 2125 A-230V



Product Description

Order Number:	2125010
Colour:	RAL 7035
Protection category IP (IEC 60 529):	IP 54
Add-ons:	With solenoid valve article no. 2125000
Approvals:	CE
Customs tariff number:	84195000
Material housing:	Mild steel, powder coated

Technical data RK 2125 A-230V

Cooling capacity L35W10 (200 l/h):	2,50 kW @ 50 Hz
	2,55 kW @ 60 Hz
Cooling capacity L35W10 (500 l/h):	3,15 kW @ 50 Hz
	3,25 kW @ 60 Hz
Refrigerant:	Water, light oils or similar
Operating temperature range:	+1°C - +72°C
Max. air volume flow:	500 m ³ /h @ 50 Hz
	530 m ³ /h @ 50 Hz
Mounting:	Internal / External
Dimensions (H x W x D):	936 x 262 x 146.5 mm
Weight:	18 kg
Rated operating voltage / frequency:	230 V 50/60 Hz ~N
Rated current:	0.7 A / 0.9 A
Starting current:	1.2 A / 1.3 A
Power consumption:	200 W
Max. Working pressure water circuit:	10 bar
Water connection:	Rp 1/4" - inside thread with 2 connectors for pipe internal diameter of 10mm
Fuse rating:	5 A (T)
Connection:	Connection terminals


Click the graphics to download the originals.

More CAD graphics can be found on our [Products Downloads page](#).


> [Overview product group Air-Water Heat Exchangers](#)

Performance Graph:

? T = Temperature difference between air intake and cooling
 P = Cooling capacity



[click image to enlarge](#)

Airflow diagram:


[click image to enlarge](#)

Cutout diagram:


[click image to enlarge](#)

[Datasheet](#) created 22.07.2015 (15:41:23). Technical rights reserved.